

Claims

1. A carcass structure for vehicle wheel tyres, comprising:
at least a carcass ply (3) comprising a first and a second series of strip-like
segments (13, 14) consecutively arranged along the circumferential development
of the carcass structure (2), each of which extends according to a substantially
5 "U" shaped conformation and comprises at least two filiform element (15)
positioned longitudinally and parallel to each other and at least partially coated
by at least a layer of raw elastomeric material (18), and
a pair of annular reinforcing structures (4) each engaged in proximity to a
respective interior circumferential edge of the carcass ply (3),
10 characterised in that each of said annular reinforcing structures (4) comprises at
least a primary portion (4a) presenting an axially interior side oriented towards
terminal edges (19a) of the segments belonging to the first series (13) and an
axially exterior side oriented towards terminal edges (20a) of the segments
belonging to the second series (14), and
15 at least an additional portion (24) positioned against the terminal edges (20a) of
the strip-like segments belonging to the second series (14), on the opposite side
relative to said primary portion (4a) of the annular structure itself; wherein said
primary portion comprises
a first circumferentially inextensible annular insert (23) shaped substantially in
20 the manner of an annulus positioned coaxially to the carcass structure (2) and
adjacently to an interior circumferential edge of the carcass ply (3), said first
annular insert (23) being formed by at least an elongated element extending
according to concentric turns (23a);
a filling body (25) made of elastomeric material presenting a side united to the

first annular anchoring insert (23);

at least a second circumferentially inextensible annular insert (24) shaped substantially in the manner of an annulus, formed by at least an elongated element extending according to concentric turns (23a) and positioned coaxially to the carcass structure (2) in a position set axially side by side to the filling body (25) and laterally opposite relative to the first annular insert (23);

and wherein said additional portion (24) comprises at least a third circumferentially inextensible annular insert (26) shaped substantially in the manner of a circular crown, formed by at least an elongated element extending according to concentric turns and positioned coaxially to the carcass structure (2) and adjacently to an interior circumferential edge of the carcass ply (3).

2. A carcass structure as claimed in claim 1, wherein said first and second series of strip-like segments (13, 14) are arranged in mutually alternated sequence along the entire circumferential development of the carcass structure.

3. A carcass structure as claimed in claim 2, wherein each of said strip-like segments (13, 14) presents two lateral portions (19, 20) developing substantially towards a geometric axis of said carcass structure in positions that are mutually distanced in the axial direction, and a crown portion (21, 22) extending in a radially exterior position between the lateral portions (19, 20), the crown portions (21, 22) belonging respectively to the segments of the first and second series (13, 14) being set mutually side by side along their circumferential development of the carcass structure (2).

4. A carcass structure as claimed in claim 1, characterised in that said third

and second annular insert (24, 26) present each a lesser radial extension than the radial extension of the first annular insert (23).

5. A carcass structure as claimed in claim 4, wherein the third
5 circumferentially inextensible annular insert (26) presents a lesser radial extension ranging between $1/3$ and $2/3$ of the radial extension of the first circumferentially inextensible annular insert (23).

6. A carcass structure as claimed in claim 4, wherein the second
10 circumferentially inextensible annular insert (24) presents a lesser radial extension ranging between $1/3$ and $2/3$ of the radial extension of the first circumferentially inextensible annular insert (23).

7. A carcass structure as claimed in claim 1, further comprising an auxiliary
15 filling body (27) made of elastomeric material situated in an axially exterior position against said at least one carcass ply and extending radially away from said third annular insert (26).

8. A carcass structure as claimed in claim 6, wherein the hardness value of
20 the auxiliary filling body (27) is substantially equal to the hardness of the filling body (25).

0937601.092801
T08260 T092660